

viscount®

NEW

V3.12 A Dlx / V3.12 A

*New, Lightweight,
Class D Active Speakers!*



The V3.12A it's the ideal solution for high quality installations in churches and auditoriums . Compact and lightweight, this new self-powered speaker features two Class D amplifiers and state-of-the art electroacoustic components able to deliver outstanding sound quality, great sound pressure and incredible linearity. Expressly developed for the use with Classical organs, the V 3.12 A offers an on-board professional equalizer, a remote power switch feature and an innovative power saving mode.

V3.12 A Dlx / V3.12 A

Technical Specifications

| | |
|-----------------------------|---|
| Total Power: | 280 Watt Continuous Power |
| Amplifier: | Class D 2 x 90 Watt rms |
| Distortion: | < 0,05% up to 75 Watt rms / 4 Ohms @ 6.67 KHz |
| Input Impedance: | 15 KOhm (balanced) |
| Input Sensitivity: | 0 dB (0,775 V) |
| Max SPL: | 118 dB (Free space) |
| Frequency Response: | 38-18000 Hz (+/- 3 dB) |
| Crossover Frequency: | 800 Hz @ 24 dB / oct. active - 2800 Hz @ 18 dB / oct. passive |
| Loudspeakers: | 1 Woofer (12") - 1 Mid Range (8") and 1 Tweeter |
| Controls : | Master Volume - Equalizer (Low - Mid Gain - Mid Freq.- High) Remote Control (12 V D.C.) - Energy Save Function |
| Connections: | 1 Input Jack - 1 Link Jack |
| Cabinet: | V3.12A Dlx - Wood veneered dark oak V3.12A - Laminated dark oak finish |
| Dimensions: | (h x w x d) 42x36x65 cm |
| Weight: | (Kg) 24 |

